

Rough Terrain Forklift

Used Rough Terrain Forklift San Bernardino - Broadly defined, a forklift truck uses two forks to load, transport and unload material. Forklifts fall into two main categories, industrial forklifts and rough terrain forklifts. Industrial forklifts are mainly used in loading docks and warehouse applications with smooth and level surfaces. Rough terrain forklifts are better suited for rocky environments and uneven surfaces. Commonly found at exterior construction sites, rough terrain forklifts have the tires, size and weight capacity to handle heavy loads. The main difference between rough terrain and industrial forklifts is the cushion tires that are on industrial forklift models. Pneumatic tires are utilized by rough terrain models. They are similar to tractor tires that offer more traction and flotation. Industrial forklifts are commonly powered by internal combustion engines although a fuel cell or battery electrical source may be used. Internal combustion engines are mainly used by rough terrain units. Types of Class 7 Rough Terrain Forklift Trucks

The three types of Class 7 Rough Terrain Forklift Trucks include the rotating telehandler forklifts, telehandler forklifts and straight mast forklifts. Every rough terrain forklift truck is designed to operate on disturbed ground and difficult locations commonly found in military and construction atmospheres. The rough terrain models travel and perform well in difficult locations. Safety considerations are taken into account for rough terrain locations with raising loads in difficult environments to keep the operator safe from tipping over. For safety reasons, it is vital the forklift maintains stability before moving, lifting or lowering. Stability of ground and knowledge of proper lifting technique is essential for safe operation of rough terrain forklifts.

Straight Mast Forklifts Straight mast forklifts are designed to transport building materials around a range of rough terrain sites such as demolition and construction sites. Pneumatic cushion tires allow this forklift better maneuverability and accessibility around difficult terrain. Uneven ground and rough surfaces are no match for pneumatic tires. Most straight mast forklift units have 2WD or 4WD configurations. Even though these machines are better utilized in exterior locations, many straight mast forklifts operate with propane or diesel, enabling them to be used indoors for short timeframes. Straight mast forklifts have a similar lift capacity compared to standard forklift models; ranging from 5K to 36K lbs.

Telehandler or Telescopic Handler Forklifts Telehandler or telescopic handler forklift trucks are equipped with a telescoping boom, giving them their name. This specially designed boom allows the forklift truck to pick up loads and place them at differing heights in front of the unit. The operator can achieve enhanced flexibility with better reach during load placement. Featuring two wheels found at the front and two wheels at the rear, the standard telehandler is a long and low machine. The telescopic boom can be found at the back of the forklift, mounted on a pivot that is attached many feet higher than the frame of the unit. The left side of the machine houses the cab and the hydraulic fluid tank and the fuel tank are found opposite to the cab. Along the center of the machine, the engine and transmission can be found inside the frame. This common configuration allows for a balanced forklift which is necessary for the basic stability of the machine which lifting, transporting and lowering loads. Telehandler units offer significantly higher lifting heights compared to standard units. Otherwise known as high-reach telehandlers or compact telehandlers, these models perform. Compact telehandlers can extend their full load capacity from eight-teen feet and the high-reach models to fifty-six feet. The load capacities of these machines range from five thousand pounds to twelve thousand pounds. All-wheel steering is popular for all-terrain forklifts and provides increased maneuverability. Thanks to steering features including power-shift transmission, the operator can maneuver the machine in excellent proximity to the work location. The latest telehandler models feature ergonomic upgrades for ultimate operator comfort. These features include tilted steering options and roomier cabs to increase operator comfort. These ergonomic upgrades have been shown to lessen repetitive stress injuries and lessen operator fatigue. A single joystick is a common design for most telehandlers. The joystick is essential for controlling the boom functions and the hydraulics responsible for forward operation.

Telehandler forklifts can also be equipped with non-marking tires which allow them to be used in other applications such as the installation of signs and billboards as well as maintenance on buildings and stadiums. Rotating Telehandler or Roto Telescopic Handler Forklifts Rotating telehandler or roto telescopic handler forklifts have many features in common with the standard telehandler forklift. Telehandlers are capable of rotating heavy-lift weights to tremendous heights. The turntable or rotating ability add extra panache. Rotating the forklift a complete three-hundred-and-sixty degrees creates a larger working location without the need of repositioning the forklift. Because of this additional feature, rotating telehandlers often have a second joystick to allow operation of the rotation function apart from the lift function. As with the standard telehandler forklift, rotating telehandlers are available with added features including power assist steering, four-wheel drive and minimized slip differential on the rear axle to boost traction and for additional safety. With the added rotating ability of these forklifts, comes additional safety considerations. Because of this, rotating telehandler rough terrain forklifts come with stabilizers to increase the safety when rotating loads from one side of the forklift to the other. There are some rotating telehandlers that are designed to move heavy weights without stabilizers to reduce the time it takes to reposition the forklift for work in other areas of the jobsite. Rotator telehandler units are typically smaller than standard telehandlers with their fixed-cab design. Therefore, rotator telehandler units can access smaller loads when compared to standard telehandler units. Ranging between four thousand and ten thousand pounds, rotating telehandlers can reach lift heights from 15 to 80 feet. Both telehandlers and rotator telehandlers can be used as a crane when fitted with a winch attachment. This means that these forklifts can sometimes allow a project to forego the need for a crane at the jobsite, saving time, expense and workspace. Advancements for Rough Terrain Forklifts Many attachments are currently available for rough terrain forklifts, such as booms, winches, rotating fork carriages and articulating booms. Because of the importance of forklift attachments in their ability to adapt forklifts to many different types of specific jobs, it is expected that the creation and availability of new rough terrain forklift attachments will continue to increase. However, the bulk of advancements are expected to be in the form of safety features, built-in to manufactured rough terrain forklifts. Some new safety features have already been developed such as automatic load restriction devices. This system weighs a load automatically and then calculates the safe reach distance of the load while considering the extension and boom angle. An alarm sounds once the safe distance is reached, warning the operator to make load weight, reach distance or boom angle adjustments.